

CLASS-LEADING PRODUCTIVITY



XES SYNERGIX 8825 PRINTER

The XES Synergix 8825 Printer brings you picture perfect images at turnaround times up to 5 times faster than the average inkjet printer and twice as fast as competitive wide-format LED printers making it the preferred solution for engineering workgroups. This highly affordable solution for on demand printing can handle the most detailed CAD imagery exhibiting output with sharp resolution, even down to single pixel lines, perfect for both internal distribution and critical customer sets.

Maximize Productivity. To maximize your productivity XES incorporates a suite of client software for the embedded AccXES™ Controller. AccXES processes files and sends them to the printer, automatically scaling and rotating your image eliminating the need to trim prints - providing true “unattended operation”.

Designed to be Environmentally Friendly. Unique Xerox patented development technology eliminates the need to change developer by reclaiming the charged toner. This process lowers maintenance costs, maximizes uptime and enhances printer output making it the ideal solution for your work environment.

XES SYNERGIX 8825 DIGITAL SOLUTION - SCALABLE AND UPGRADABLE

Combine the 8825 Printer with the Synergix Scan System and the AccXES Controller, to create a scalable solution capable of concurrently printing and scanning or copying. The system allows you to improve hardware performance with simple installation of software upgrades downloadable via the web.

The XES Synergix 8825 Digital Solution is a complete system that will seamlessly integrate into your network, meeting your workgroup needs now and in the future. It is designed to both simplify work processes and improve productivity - delivering integrated network printing, scanning and digital copying at the touch of a button.

MORE FEATURES THAN ANY OTHER SYSTEM IN ITS CLASS

- Intuitive control panel allows for simple walk up copying
- Preset modes for line, photo and mixed documents
- 1 or 2 roll media supply options for excellent flexibility in A - E sizes
- Time saving features include job recall, electronic collation and auto reduction and enlargement
- Optional monochrome scanning speed upgrade from 2 to 4 ips; monochrome scan-to-net (includes scan-to-PDF) and color scan-to-net for JPEG/TIFF.



- **Delivers true 400 dpi resolution and 128 greyscales**
- **Prints up to 7 D-size images per minute**
- **AccXES Controller allows seamless linking to XES scanning and finishing equipment**



XES SYNERGIX 8825 PRINTER/DIGITAL SOLUTION

Features

Auto port sensing, Auto data format recognition, Auto scaling, Auto rotation, Auto size detection, Auto roll select and switch, Remote printer administration, Prioritized job queuing, Remote job queue management, Electronic collation, 9 pen palettes (256 pens each), 64 pen patterns, including 15 user-definable patterns, Plot labeling with automatic naming and time/date generation, Banner pages, Page composition/plot overlay, Plot stamping with user-downloadable stamps, 10 user setups, 128 gray scales, Media mismatch management, Plot nesting

SPECIFICATIONS

Synergix 8825 Printer

| | |
|-----------------------|---|
| Process / Imaging | Xerographic LED |
| Photoreceptor | Organic |
| Media Supply | 1 Roll, 500 ft Optional - 2nd roll; Cut sheet bypass |
| Media Type | Bond, Vellum and Film |
| Output Size | Min 8 1/2 x 11 inches, Max 36 inches x 80 feet |
| Resolution | 400 dpi |
| Process Speed | 3 ips |
| Throughput | Up to 7 D / 3.5 E's per minute |
| Power Requirements | 60 Hz: 115 V/16A 50-60 Hz: 220/230-240 V/10A |
| Weight | Approx. 550 lbs |
| Dimensions | W 57" H 43" D 23" |
| Finishing | Standard - Catch Tray - 50 E / 100 D Optional - Online Folder Optional - Stacker 1000 - up to 1000 mixed size prints |
| Safety Certifications | UL 1950, CNL C22.2 No. 950-M93, Low Voltage Directive 72/23/EEC, CE Marking Directive 93/68/EEC, FCC Part 15 Subpart B (Class A), ICES-003, Issue 3: 1997 (Class A), EMC Directive 89/366/EEC |

AccXES™ Controller

| | |
|-------------------|---|
| CPU | Power PC |
| Power | 110/220 V |
| Memory | 128 Mb standard; Expandable to 512 Mb |
| Hard Disk | Standard - 20 IDE ATA100 |
| Data Formats | HP-GL; HP-GL/2; HP-RTL; CGM (Level 1 with ATA ext.); C4; FileNET; XES 150 Emulation; Versatec Data Standards (VRF, ordered vector, blocked raster, compacted raster); CalComp 906/907/951/PCI; TIFF 6.0; NIRS; CALS 1 & 2; VCGL; Compression types (for applicable raster formats): CCITT G4, G3-1D, G3-2D, Packbits, RLE, Seed Row, Adaptive; JPEG; Optional Adobe PostScript 3 with PDF support |
| Interfaces | Standard - Serial RS-232, IEEE 1284 Bi-directional Centronics; 10/100 Ethernet (TCP/IP) supports 10/100 BaseT Optional - Ultra wide SCSI; External print server |
| Network Protocols | Standard - TCP/IP with lpr/lpd Optional - Novell, Ethernalk, NetBEUI and others supported through external print server |
| Client Software | ADI and HDI print drivers for AutoCAD R14, AutoCAD 2000, 2000i, 2002 Print drivers for Windows 95/98/NT/2000/XP Web Printer Manager Tool using Netscape Navigator 4 or Microsoft IE 4 or later Document Submission Tool for Windows 95/98/NT/2000 and Solaris Optional - Adobe PostScript 3 drivers for Windows 95/98/NT/2000 |

Synergix Scan System

| | |
|--------------------------------------|--|
| Resolution | 400 x 400 dpi |
| Copy / Scan Speed | 2 ips at 400 dpi (copy and scan) 4 ips at 200 dpi (scan) |
| Color Scan-to-Net | .5 ips at 400 dpi 1.0 ips at 300 dpi Formats: TIFF, JPEG |
| Input | Min 4 1/2 x 5 1/2 inches Max 42 inches (only captures 36" of image) x 100 feet Thick documents up to 1/2 inch |
| Edge / Center Adjustment Scan-to-Net | Lead and trail edge adjust / center alignment Optional - Indexing; Scan preview; Link to raster editor; Resolution selection; TIFF 6.0, CALS, JPEG or PDF data format; TCP/IP Ethernet interface; Line or grayscale modes |
| Power Requirements | 50/60 Hz; 120/240 V; 10A |
| Dimensions | W 53" H 45" D 16" with Stand |
| Safety Certifications | UL 1950, CNL C22.2 No. 950-M93, Low Voltage Directive 72/23/EEC, CE Marking Directive 93/68/EEC, FCC Part 15 Subpart B (Class A), ICES-003, Issue 3: 1997 (Class A), EMC Directive 89/366/EEC |

Copier

| | |
|-------------------------|---|
| Reduction / Enlargement | 25 to 400% in 0.1% increments |
| Output Selection | Auto/manual roll selection and scaling |
| Concurrency | Scanning/copying/printing; Printer interrupt key |
| Digital Retention | Up to 999 copies from a set of at least 100 standard E size drawings |
| Sets Build | Electronic collation; Forward; Reverse; Last job recall; Rescale and reprint without rescanning; 999 copies; Batch mode |
| Imaging | Inverse, Mirroring; Transform; Rotation; 7 copy contrast levels |
| Image Quality | Automatic dynamic background suppression / Automatic width detection of original |
| Copy Modes | Line; Mixed; Photo |
| Client Software | Document Retrieval Tool for Windows 95/98/NT/2000 and Solaris |

Options

Scan-to-Net, 4 ips (at 400 dpi) scanner speed upgrade, Compact scanner catch tray, External print server, Expandable memory to 512 Mb, Adobe PostScript 3 (includes PDF support), Account Data Tracking, Stacker 1000, Online Folder, Color Scan-to-Net.

Supplies ordering

XES offers a broad array of media, toner and consumables designed to work with all brands of wide-format equipment. For the most current supplies listing visit www.reproequipsvc.com or call your supplies representative at 1-713-270-0022.

Specifications are subject to change without notice.



Xerox®, Synergix, AccXES™, 8825, the digital box icon and the acronym XES are trademarks of Xerox Corporation. Adobe is a registered trademark and PostScript 3 is a trademark of Adobe Systems Incorporated. ©XESystems, Inc. 2002. All other product names mentioned herein are trademarks of their respective companies. All rights reserved.
Printed in the USA on recycled paper. 610P70658B